DPU 3060H

Reversible vibratory plate

Maximum compaction in the tightest spaces

The lightweight reversible vibratory plates are powerful and versatile making them ideal for base preparation, gardening, landscaping and maintenance work on streets, roads and parking lots. The Wacker Neuson vibratory plates in the 25-37 kN class come equipped with a sturdy, integrated wheel set. This unique feature provides mobility on the construction site.

Highlights

- Compact dimensions, high performance
- Integrated wheel set
- Sturdy and durable

Technical Data

Mechanical - Output Details

Centrifugal force	30 kN
Area capacity	648.0 m2/h
Forward Running	18.0 m/min
Gradeability	46.6 %
Vibrations (Hz)	90.0 Hz

Mechanical Details

Length Baseplate	703.0 mm
Width	600.0 mm
Width Baseplate	600.0 mm
Height	1,101.0 mm
Height Cover frame	777.0 mm
Thickness Baseplate	10.0 mm
Operating weight	190.0 kg
Ground clearance	777.0 - 887.0 mm

Engine

Effective power	4.2 KW
Nominal Engine speed	2,800.0 1/min

Environment Data

HAV summation (average value)	3.2 m/s2
HAV summation (Standard)	EN 500-4

Electrical System

Coding options	0
Remote Control Range	0.0 m

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2025 Wacker Neuson SE | www.wackerneuson.com

Available engines

Hatz 1B30-2-310A

Cooling	air cooling
Engine type	Diesel engine
Engine operating mode	four-stroke
Cylinder	1
Cylinder capacity	347 cm3
Fuel	Diesel EN 590
Fuel consumption	0.60 L/hr
Tank capacity	5.00 l
Starter type	Recoil starter
Engine Manufacturer	Hatz

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2025 Wacker Neuson SE | www.wackerneuson.com

DPU 3060H-TS

Reversible vibratory plate

Fast and efficient when vibrating paving stones

The lightweight reversible vibratory plates are powerful and versatile making them ideal for base preparation, gardening, landscaping and maintenance work on streets, roads and parking lots. The Wacker Neuson vibratory plates in the 25-37 kN class come equipped with a sturdy, integrated wheel set. This unique feature provides mobility on the construction site.

Highlights

- Top-speed version
- Compact dimensions, high performance
- Integrated wheel set
- Sturdy and durable

Technical Data

Mechanical - Output Details

Centrifugal force	30 kN
Area capacity	792.0 m2/h
Forward Running	22.0 m/min
Gradeability	46.6 %
Vibrations (Hz)	90.0 Hz

Mechanical Details

Length Baseplate	703.0 mm
Width	600.0 mm
Width Baseplate	600.0 mm
Height	1,101.0 mm
Height Cover frame	777.0 mm
Thickness Baseplate	10.0 mm
Operating weight	190.0 kg
Ground clearance	777.0 - 887.0 mm

Engine

Effective power	4.2 KW
Nominal Engine speed	2,800.0 1/min

Environment Data

HAV summation (average value)	3.3 m/s2
HAV summation (Standard)	EN 500-4

Electrical System

Coding options	0
Remote Control Range	0.0 m

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2025 Wacker Neuson SE | www.wackerneuson.com

Available engines

Hatz 1B30-2-310A

Cooling	air cooling
Engine type	Diesel engine
Engine operating mode	four-stroke
Cylinder	1
Cylinder capacity	347 cm3
Fuel	Diesel EN 590
Fuel consumption	0.60 L/hr
Tank capacity	5.00 l
Starter type	Recoil starter
Engine Manufacturer	Hatz

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2025 Wacker Neuson SE | www.wackerneuson.com

DPU 3060HE-TS

Reversible vibratory plate

Fast and efficient when vibrating paving stones

The lightweight reversible vibratory plates are powerful and versatile making them ideal for base preparation, gardening, landscaping and maintenance work on streets, roads and parking lots. The Wacker Neuson vibratory plates in the 25-37 kN class come equipped with a sturdy, integrated wheel set. This unique feature provides mobility on the construction site.

Highlights

- Top-speed version
- Compact dimensions, high performance
- Integrated wheel set
- Sturdy and durable

Technical Data

Mechanical - Output Details

Centrifugal force	30 kN
Area capacity	792.0 m2/h
Forward Running	22.0 m/min
Gradeability	46.6 %
Vibrations (Hz)	90.0 Hz

Mechanical Details

Length Baseplate	703.0 mm
Width	600.0 mm
Width Baseplate	600.0 mm
Height	1,101.0 mm
Height Cover frame	777.0 mm
Thickness Baseplate	10.0 mm
Operating weight	215.0 kg
Ground clearance	777.0 - 887.0 mm

Engine

Effective power	4.2 KW
Nominal Engine speed	2,800.0 1/min

Environment Data

HAV summation (average value)	3.3 m/s2
HAV summation (Standard)	EN 500-4

Electrical System

Coding options	0
Remote Control Range	0.0 m

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2025 Wacker Neuson SE | www.wackerneuson.com

Available engines

Hatz 1B30-2-311A

Cooling	air cooling
Engine type	Diesel engine
Engine operating mode	four-stroke
Cylinder	1
Cylinder capacity	347 cm3
Fuel	Diesel EN 590
Fuel consumption	0.60 L/hr
Tank capacity	5.00 l
Starter type	Recoil starter
Engine Manufacturer	Hatz

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2025 Wacker Neuson SE | www.wackerneuson.com