IRSEN38/042

High-frequency internal vibrators

Concrete consolidation with comfortable operation

The Wacker Neuson IRSEN series of high-frequency internal vibrators offer a short protection hose and low vibration handle. The ergonomically designed handle with vibration damping offers a high degree of comfort during operation. Wacker Neuson's IRSEN high-quality internal vibrators offer a variety of features and benefits.

Highlights

- Handle (Low Vib)
- High-performance electric motor with stable speeds
- Made in Germany
- Sturdy design

Technical Data

Electrical - Output Details

Nominal current	7.00 A
Nominal voltage	42.0 V
Nominal frequency	200.0 Hz
Nominal power [P]	0.41 KW
Phase	3.0 ~

Mechanical - Output Details

Amplitude at air	1.900 mm
Vibrations	12,000.0 1/min
Vibrations (Hz)	200.0 Hz

Mechanical Details

Length Hose	0.8 m
Weight	5.90 kg
Rubber cap	no

Motor

Motor type	Asynchronous motor

Environment Data

Protection class	III / Safety extra-low voltage
Degree of protection	IP67

Electrical System

Breaker Switch On/Off	Yes
Integrated transformer	No
Length Cable	15.0 m
Kind of plug	CEE-Plug 3P 32A 42V 4H

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2025 Wacker Neuson SE | www.wackerneuson.com