



PST2-400

PS series (230 V, 1~) submersible trash-water pumps

Heavy-duty and durable for demanding dewatering tasks

The lightweight, portable PS series of electric submersible pumps can transport dirty water with particulate matter up to 9.5 mm. They are suitable for a variety of applications, including building, civil engineering, municipal work, horticulture and landscape construction. They are extremely durable and easy to use. The high-quality pumps ensure long service life and the variety of PS pump models meet the needs of a wide range of applications.

Highlights

- Variety of models
- Bottom suction plate for PST2 400
- Reliable protection against water creepage
- Perfect sealing of the engine compartment by double, internally placed mechanical seal made of silicon carbide in the oil bath
- Oil lifter for reliable lubrication in any situation
- Safe to run dry
- Steel sleeve reduces wear of the shaft

Technical Data

■ Electrical - Output Details

Nominal voltage	230.0 V
Nominal frequency	50.0 Hz
Starting current Idle running	7.0 A
Starting current full load	2.6 A
Phase	1.0 ~

■ Mechanical - Output Details

Flow rate max.	200.0 l/min
Solid diameter max.	9.5 mm
Delivery height max.	12.0 m

■ Mechanical Details

Length	265.0 mm
Width	185.0 mm
Height	330.0 mm
Operating weight	11.3 kg
Intake-/Pressure socket-dia.	50.0 mm

■ Motor

Nominal speed	3,000.0 1/min
---------------	---------------

■ Electrical System

Length Cable	10.0 m
Cable cross-section	1.0 mm ²



PST2-400

PS series (230 V, 1~) submersible trash-water pumps

Heavy-duty and durable for demanding dewatering tasks

The lightweight, portable PS series of electric submersible pumps can transport dirty water with particulate matter up to 9.5 mm. They are suitable for a variety of applications, including building, civil engineering, municipal work, horticulture and landscape construction. They are extremely durable and easy to use. The high-quality pumps ensure long service life and the variety of PS pump models meet the needs of a wide range of applications.

Highlights

- Variety of models
- Bottom suction plate for PST2 400
- Reliable protection against water creepage
- Perfect sealing of the engine compartment by double, internally placed mechanical seal made of silicon carbide in the oil bath
- Oil lifter for reliable lubrication in any situation
- Safe to run dry
- Steel sleeve reduces wear of the shaft

Technical Data

■ Electrical - Output Details

Nominal current	2.60 A
Nominal voltage	230.0 V
Nominal frequency	50.0 Hz
Phase	1.0 ~

■ Mechanical - Output Details

Flow rate max.	210.0 l/min
Solid diameter max.	7.0 mm
Delivery height max.	12.2 m

■ Mechanical Details

Length	265.0 mm
--------	----------

Width	185.0 mm
Height	330.0 mm
Operating weight	11.3 kg
Intake-/Pressure socket-dia.	50.0 mm

■ Motor

Nominal speed	3,000.0 1/min
---------------	---------------

■ Electrical System

Length Cable	10.0 m
Cable cross-section	1.0 mm ²